



α - угол контакта.

Основные размеры подшипников					
Международное обозначение	Стандарт ISO	Обозначение	Размеры, мм	Масса, кг	
Серия ширин		0	, серия диаметров	1	
36016K6	-		6	17	6
36017K6	-		7	19	6
36018K6	-		8	22	7

36019K6	-	9	24	7
36100K6	-	10	26	8
36101K6	-	12	28	8
36102K6	-	15	32	9
36103K6	-	17	35	10
36104K6	-	20	42	12
36105K6	-	25	47	12
36106K6	-	30	55	13
36107K6	-	35	62	14
36108K6	-	40	68	15
36109K6	-	45	75	16
36110K6	-	50	80	16

36111K6	-	55	90	18
36112K6	-	60	95	18
36113K6	-	65	100	18
36114K6	-	70	110	20
36115K6	-	75	115	20
36116K6	-	80	125	22
36117K6	-	85	130	22
36118K6	-	90	140	
36120K6	-	100	150	24
36122K6	-	110	170	28
36124K6	-	120	180	28

36126K6	-	130	200	33
36128K6	-	140	210	33
36130K6	-	150	225	35
36132K6	-	160	240	38
36134K6	-	170	260	42
36136K6	-	180	280	46
Серия ширин	0	, серия диаметров		2
36027K6	-	7	22	7
36028K6	-	8	24	8
36029K6	-	9	26	8
36200K6	-	10	30	9
36201K6	-	12	32	10

36202K6	-	15	35	11
36203K6	-	17	40	12
36204K6	-	20	47	14
36205K6	-	25	52	15
36206K6	-	30	62	16
36207K6	-	35	72	17
36208K6	-	40	80	18
36209K6	-	45	85	19
36210K6	-	50	90	20
36211K6	-	55	100	21
36212K6	-	60	110	22

36213K6	-	65	120	23
36214K6	-	70	125	24
36215K6	-	75	130	25
36216K6	-	80	140	26
36217K6	-	85	150	28
36218K6	-	90	160	30
36219K6	-	95	170	32
36220K6	-	100	180	34
36222K6	-	110	200	38
36224K6	-	120	215	40
36226K6	-	130	230	40
36228K6	-	140	250	42

36230K6	-	150	270	45
36232K6	-	160	290	48
36234K6	-	170	310	52
36236K6	-	180	320	52

Масса подшипников рассчитана для плотности стали 7,85 кг/дм³.

[Promogirl](#)